



**ADHESIVE (VOC)**



Available in 10 oz and  
28 oz tubes

## SRW VOC RETAINING WALL & PAVER ADHESIVE

**SRW VOC Retaining Wall & Paver Adhesive** is a professional strength, VOC compliant formula specially designed for masonry, concrete, brick, block, pavers and common landscaping materials. It can even be used to bond wet, frozen or damp surfaces.

- Ideal for wet or frozen surfaces
- Extrudes well in low temperatures
- Provides a strong, durable bond
- Waterproof
- Meets State and Federal VOC regulations

### DIRECTIONS

1. Surfaces should be clean and free from oil, grease, excessive water, ice or any other material which may deter adhesion.
2. Cut tip on slant for 1/4" or 3/8" bead. Puncture inner seal with nail or wire. Place cartridge in a caulking gun.
3. Apply adhesive with the caulking gun to only one of the surfaces to be joined. Apply in a continuous bead to ensure complete coverage. Apply no more adhesive than you can cover in 20 minutes.
4. Press surfaces together firmly with a slight twisting motion. For faster curing, lift the cap, stone, paver or brick straight up to "flash" or expose adhesive to the air and reset. Do not twist as you lift.
5. Vertical or slanted applications may require additional bracing until adhesive has dried.
6. Allow 48-hour cure time and 4-5 days before walking on any steps or heavy traffic areas.

**Cleanup** • Scrape off dried excess adhesive with a putty knife. Remove residue with mineral spirits. (Note: Test cleaning solvent on an out-of-way area to make sure it will not mar the surface to be cleaned.)

### USER TIPS

- On tumbled products, make sure surface is clean of any dust, dirt or material that may deter proper adhesion. We recommend using a 3/8" bead.
- On grooved materials, make sure you have a full positive connection of adhesive to both surfaces.
- Not recommended to apply in temperatures below 10°F.
- Do not use below the waterline or for continuous submersion. Not recommended for fiberglass, rubber, plastic or foam.

## PACKAGING

PART NUMBER	SIZE	# PER CARTON OR PALLET	LBS
AP10	10 oz	12/case; 64 cases/pallet	12/case 818/pallet
AP28	28 oz	12/case; 38 cases/pallet	29/case 1152/pallet

## STORAGE

SRW Adhesive can be stored more than 12 months in tightly closed container at 75°F. Do not store in direct sunlight for extended periods of time. Store in the upright position when possible.

## GUIDELINES & COVERAGE

### Application Temperatures:

0° - 120° F, for adhesives and substrates

**Method of application:** Cartridge/caulking gun. Due to fast-drying characteristics, it is not practical to apply by trowel. Strong initial tack allows light pieces to be bonded with only momentary pressure.

**Working time:** About 30 minutes for 1/4" bead.

### Coverage:

Approximate length of bead according to container size and bead diameter		
Bead Size	10 oz VOC	28 oz VOC
1/4" bead	32 ft.	89 ft.
3/8" bead	14 ft.	35 ft.

## WARNINGS

This product is VOC compliant, if needed, a regular adhesive is available, please contact SRW.

### KEEP OUT OF REACH OF CHILDREN.

EXTREMELY FLAMMABLE. VAPOR HARMFUL. Contains acetone, hexane and toluene. Keep away from heat, sparks & flame. Use only with positive cross-ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye and skin irritation. Prolonged or repeated overexposure to solvents in uncured product can cause central nervous system, peripheral nervous system, eye, skin, liver, kidney or respiratory system effects. (See Material Safety Data Sheet)

### Important Notice:

Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied is made for the merchantability, fitness or suitability for the use of this product or otherwise extending beyond the description hereof except the obligation to replace that product for portion of shipment proved defective. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use. Liability is limited to product replacement only.