



solid solutions to better hardscapes

PO Box 70 • 32020 126th St • Princeton, MN 55371 • Tel 800-752-9326 • Fax 763-389-2725

SRW DF2

SRW Products Manufactures/Supplies a 100% Polyester Non-Woven Thermal Bonded Filament Fibers marketed as **SRW DF2**. With excellent dimensional stability and low shrinkage, our drainage fabrics serve as the professional's choice for drain field projects. The fabric will not rot or mildew, is non-biodegradeable with superior UV resistance, and is resistant to damage from insects and rodents.

SRW DF2 meets or exceeds the physical property values listed below.

Fabric Property	Test Method	Units	Minimum Average Roll Value
Weight (Typical)	ASTM D 5261	oz/yd ²	2.0(70gsm)
Grab Tensile	ASTM D 4632	lbs.	48/56
Grab Elongation	ASTM D 4632	lbs.	>60
Trap Tear	ASTM D 4533	lbs.	27/23
Puncture	ASTM D 4833	lbs.	18
Permittivity	ASTM D 4491	sec ⁻¹	3.93
Water Flow	ASTM D 4491	gpm/ft ²	294
AOS	ASTM D 4751	US Sieve	#50

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.