	= SECTION 1 - IDENTIFICATION ====================================
MANUFACTURER:	SRW PRODUCTS
ADDRESS:	$32005 \ 126^{\text{TH}}$ Street
ADDRESS.	Princeton, MN 55371
	PIINCeton, MN 55571
EMERGENCY PHONE:	1-800-424-9300
INFORMATION PHONE:	
	Safety Director
NAME OF TREFARER.	Salety Dilector
REVISION DATE:	01-01-2021
PRODUCT NAME:	SRW RE-RUST ELIMINATOR
PRODUCT CODE:	SSRE
CF	CTION 2 - HAZARDS IDENTIFICATION ====================================
HAZARD RISK CLASSIFICATION SIGNAL WORD: PICTOGRAM: GHS05 - CORROSION HAZARD CLASS HAZARD CATEGORY CORROSIVE TO METALS CATEGORY 1 SKIN CORROSION / CATEGORY 1 IRRITATION HAZARD STATEMENTS: H290 May be corrosive to metal. H303 May be harmful if swallowed H314 Causes severe skin burns and eye damage PRECAUTIONARY STATEMENTS: PREVENTION: P260 Do not breath dusts/fume/gas/mist/vapors or spray. P264 Wash hands and any exposed area thoroughly after handling.	
P280 Wear protective impervious gloves/ OSHA approved eye protection/face protection.	
RESPONSE:	
P301+P312 If swallowed	: Call a Poison Center / doctor if you feel unwell.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.	
P303+P361+P353 If on s	kin (or hair): Take off immediately all contaminated
clothing. Rinse skin with water (or shower).	
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for	
breathing.	
P305+P351+P338 If in eyes: Rinse cautiously with water for several	
minutes.	
Remove contact lenses, if present and easy to do. Continue rinsing.	
P310 Immediately call a POISON CENTER/doctor/ emergency responder.	
P321 Specific treatment (see on this label)	
P330 Rinse mouth.	
P363 Wash contaminated clothing before reuse.	
STORAGE :	
P405 Store locked up.	
DISPOSAL:	
P501 Store separately. Dispose of contents/ container in accordance	
with local/ regional/national /international regulations.	

=== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS === WEIGHT EXPOSURE LIMITS COMPONENT CAS NUMBER PERCENT OSHA PEL ACGIH TT.V OTHER \_\_\_\_\_ + Phosphoric Acid 7664-38-2 18.0 1 MG/M3 1 MG/M3 3 MG/M3 + Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. PRIMARY ROUTES OF EXPOSURE: Skin contact. EFFECTS OF ACUTE EXPOSURE: EYES: Corrosive to eyes. Contact with eyes may cause severe irritation and burns. SKIN: Corrosive to skin and mucous membranes. Contact with skin may cause severe irritation and burns. May be absorbed through skin in toxic amounts. INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea. INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful. Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury. CHRONIC HEALTH EFFECTS: No anticipated chronic effects. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: No known effects on other illnesses. ======= SECTION 4 - FIRST AID MEASURES ====== EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek medical attention. SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing. INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention. INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists. FLASH POINT: No flash METHOD USED: n/a FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: n/a UPPER: n/a EXTINGUISHING MEDIA: This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide. SPECIAL FIREFIGHTING PROCEDURES: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out. UNUSUAL FIRE AND EXPLOSION HAZARDS: There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers. ======= SECTION 6 - ACCIDENTAL RELEASE MEASURES =============== STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or

similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear

appropriate protective equipment.

#### ====== SECTION 7 - HANDLING AND STORAGE ==== HANDLING INFORMATION: Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communicating Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray. STORAGE INFORMATION: Keep from freezing; material may coagulate. The minimum recommended storage temperature is 34F/1C, the maximum recommended storage temperature is 120F/49C. Keep away from incompatible materials (see section 10). Keep containers tightly closed. It is advised that material be used within 1 year of manufacture, rotate stock. OTHER PRECAUTIONS: All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations. RESPIRATORY PROTECTION: No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant. VENTILATION: General room ventilation is adequate. PROTECTIVE GLOVES: Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse. EYE PROTECTION: Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI 287.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible. WORK/HYGIENIC PRACTICES: Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines. PHYSICAL STATE: Liquid COLOR: Clear (Water white) ODOR: Amine or ammonia odor SOLUBILITY IN WATER: Dilutable SPECIFIC GRAVITY (H2O=1): 1.09 VAPOR DENSITY: Heavier than air. BOILING RANGE: EVAPORATION RATE: Slower than nBuAc COATING V.O.C.: 0 g/l (0.0 lb./gal) STABILITY: Stable under normal conditions and handling. CONDITIONS TO AVOID: None known INCOMPATIBILITY (MATERIALS TO AVOID): Avoid exposure to strong oxidizing agents and reducing agents. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of

carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

HAZARDOUS POLYMERIZATION:

Will not occur.

**EXAMPLE 1 EXAMPLE 1 EXAMP** 

REVISION DATE: 02/01/11 HMIS CODES: H F R P 3 0 1 I